
Cable Ties & Banding | NYLON CABLE TIES

ZERO HALOGEN NYLON CABLE TIES



Ident & Wiring Term

Heatshrink Repair

Cable Jointing

Junction Boxes

Flexible Conduit

Cable Cleats

Earthing Lightning



Printed Electrical Metering Cable Ties

Printed Electrical Cable ties, designed for identifying cables in single and multi-phase metering installations.

- Available in industry approved colours including Black, Blue and Brown, other colours to order.
- Labelled with either L, L1, L2, L3 or N

Temperature Range: -40°C to 85°C Material: PA66 (Nylon)
Colour: Black, Blue, Brown
Flammability Rating: UL94 - V2





		Nominal			Loop Tensile		Pack
Code	Colour	Length (A)	Width (B)	Label	Max Bundle Dia.	Strength (Kg)	QTY
NTB50s-L	Black	200	4.8	L (repeated)	52	22	100
NTB50s-L1	Black	200	4.8	L1 (repeated)	52	22	100
NTB50s-L2	Black	200	4.8	L2 (repeated)	52	22	100
NTB50s-L3	Black	200	4.8	L3 (repeated)	52	22	100
NTBR50s-L	Brown	200	4.8	L (repeated)	52	22	100
NTBR50s-L1	Brown	200	4.8	L1 (repeated)	52	22	100
NTBR50s-L2	Brown	200	4.8	L2 (repeated)	52	22	100
NTBR50s-L3	Brown	200	4.8	L3 (repeated)	52	22	100
NTBL50s-N	Blue	200	4.8	N (repeated)	52	22	100