


Accessories | INDUSTRIAL AREA ADAPTORS

NYLON ADAPTORS METRIC & PG



Metric-Metric Nylon Adaptors

Remora Metric-Metric Nylon Adaptors enable the use of larger cable glands with smaller pre-existing threaded holes in machines, devices and housings.

Protection: IP56


IP66 (if fitted with sealing washer)

Temperature Range: -40°C to 100°C (static)

Material: PA6 (Nylon) Fibre Reinforced



Code	Male Thread	Female Thread	Male Thread		
			Length (L1)	A/F	Body Height
AM12M16N	M12 x 1.5	M16 x 1.5	9.0	20.0	18.0
AM16M20N	M16 x 1.5	M20 x 1.5	9.0	24.0	18.0
AM20M25N	M20 x 1.5	M25 x 1.5	9.0	29.0	18.0
AM25M32N	M25 x 1.5	M32 x 1.5	10.0	36.0	18.0
AM32M40N	M32 x 1.5	M40 x 1.5	12.0	46.0	18.0
AM40M50N	M40 x 1.5	M50 x 1.5	12.0	55.0	18.0
AM50M63N	M50 x 1.5	M63 x 1.5	14.0	68.0	18.0



PG-Metric Nylon Adaptors

Remora PG-Metric Nylon Adaptors enable the use of metric cable glands in machines, devices and housings that have a pre-existing PG threaded entry.

Protection: IP56

IP66 (if fitted with sealing washer)

Temperature Range: -40°C to 100°C (static)

Material: PA6 (Nylon) Fibre Reinforced



Code	Male Thread	Female Thread	Male Thread		
			Length (L1)	A/F	Body Height
APG7M16N	PG7 x 1.27	M16 x 1.5	9.0	20.0	18.0
APG9M16N	PG9 x 1.41	M16 x 1.5	9.0	20.0	18.0
APG9M20N	PG9 x 1.41	M20 x 1.5	9.0	24.0	18.0
APG11M16N	PG11 x 1.41	M16 x 1.5	9.0	22.0	18.0
APG11M20N	PG11 x 1.41	M20 x 1.5	9.0	24.0	18.0
APG13M20N	PG13.5 x 1.41	M20 x 1.5	10.0	24.0	18.0
APG13M25N	PG13.5 x 1.41	M25 x 1.5	10.0	29.0	18.0
APG16M25N	PG16 x 1.41	M25 x 1.5	10.0	29.0	18.0
APG21M32N	PG21 x 1.59	M32 x 1.5	12.0	36.0	18.0
APG29M40N	PG29 x 1.59	M40 x 1.5	12.0	46.0	18.0
APG36M50N	PG36 x 1.59	M50 x 1.5	14.0	55.0	18.0
APG42M63N	PG42 x 1.59	M63 x 1.5	14.0	68.0	18.0