

## BRASS DOME HEAD STOPPING PLUGS

### Metric Industrial Dome Head Stopping Plugs

- ISO Metric range.
- Also available with long thread (see table below)
- Application; Machines, Devices, Housings, Panels

**Standards:** EN 50262

**Protection:** IP54

IP66 / IP68 (if fitted with sealing washer)



**Temperature Range:** -200°C to 200°C

**Material:** Nickel Plated Brass



Code	Entry Thread	Thread Length (L1)	Cap Diameter (A)
EMVS12	M12 x 1.5	5.0	14.0
EMVS16	M16 x 1.5	5.0	18.0
EMVS20	M20 x 1.5	6.5	22.0
EMVS25	M25 x 1.5	7.0	28.0
EMVS32	M32 x 1.5	8.0	35.0
EMVS40	M40 x 1.5	8.5	44.0
EMVS50	M50 x 1.5	9.0	54.0
EMVS63	M63 x 1.5	10.0	67.0

Long Thread Code	Entry Thread	Thread Length (L1)	Cap Diameter (A)
EMVS-L12	M12 x 1.5	13.0	14.0
EMVS-L16	M16 x 1.5	13.0	18.0
EMVS-L20	M20 x 1.5	13.0	22.0
EMVS-L25	M25 x 1.5	14.0	28.0
EMVS-L32	M32 x 1.5	14.5	35.0
EMVS-L40	M40 x 1.5	14.5	44.0
EMVS-L50	M50 x 1.5	15.5	54.0
EMVS-L63	M63 x 1.5	16.5	67.0



### PG Industrial Dome Head Stopping Plugs

- PG range.
- Application; Machines, Devices, Housings, Panels

**Standards:** EN 50262

**Protection:** IP54



IP66 / IP68 (if fitted with sealing washer)

**Temperature Range:** -200°C to 200°C

**Material:** Nickel Plated Brass



Code	Entry Thread	Thread Length (L1)	Cap Diameter (A)
MV7	PG7 x 1.27	5.0	14.0
MV9	PG9 x 1.41	6.0	17.0
MV11	PG11 x 1.41	6.0	20.0
MV13	PG13.5 x 1.41	6.5	22.0
MV16	PG16 x 1.41	6.5	24.0
MV21	PG21 x 1.59	7.0	30.0
MV29	PG29 x 1.59	8.0	39.0
MV36	PG36 x 1.59	9.0	50.0
MV42	PG42 x 1.59	10.0	57.0
MV48	PG48 x 1.59	10.0	64.0



Call the Remora sales team at **01226 352 000**

Challenge us - We find a solution

Ident & Wiring Term  
Copper Lugs  
Heatshrink Repair  
Cable Joining  
Junction Boxes  
Flexible Conduit  
Cable Glands  
Gland Accs.  
Cable Cleats  
Earthing Lightning  
MCC Cable  
Cable Ties & Acc  
Tooling & Cable Prep  
Fixing & Security