



Hooks

Suspension Hooks

Galvanised Steel Suspension Hooks

Suspension Hooks are designed for holding single power cables or small cable bundles. Fabricated from mild steel flat 6mm bar, hot dipped galvanised to BS EN ISO 1461:1999. Special designs are available on request. The recommended safe working load for each hook is shown below.

- Holding single cables or small bundles to walls or supports structures
- Superior strength tensile strength
- Excellent stiffness


Temperature Range: -40°C to 150°C

Material: Mild Steel Hot Dipped Galvanised



Safe Working Load: 200 kg




Code	Cable Range		Dimensions			Fixing		Weight	
	Min	Max	(A)	(U)	(W)	Hole (mm) (V)	Thickness	(g)	
SHA1	-	50.0	105.0	25.0	40.0	11.0	6.0	320	
SHA2	51.0	75.0	120.0	25.0	50.0	13.0	6.0	490	
SHA3	76.0	100.0	155.0	25.0	50.0	13.0	6.0	1,300	
SHB1	-	50.0	125.0	55.0	40.0	11.0	6.0	440	
SHB2	51.0	75.0	140.0	60.0	50.0	13.0	6.0	680	
SHB3	76.0	100.0	150.0	60.0	50.0	13.0	6.0	780	
SHC1	-	50.0	125.0	40.0	40.0	13.0	6.0	460	
SHC2	51.0	75.0	140.0	45.0	50.0	13.0	6.0	700	
SHC3	76.0	100.0	150.0	45.0	50.0	13.0	6.0	780	



Type SHA



Type SHB



Type SHC