Cable Glands ARMAKIT® CABLE GLANDS

INDOOR/OUTDOOR - ALUMINIUM WIRE ARMOUR

Industrial Grade Low Smoke

Aluminium Wire Armour

Low Smoke and Acid Fume Emission

CW Ali ArmaKit

The ArmaKit® CW Ali Gland is a three-part gland designed for use with Aluminium Wire Armoured PVC and LS cables. The integral polychloroprene environmental seal provides full protection against high power jets of liquid and is 100% dust tight. The separate cone-and-ring design of the three-

part ArmaKit® CW Ali Gland prevents twisting of the armour wires during installation and an internal aluminium washer ensures the seal will not deform






as the glands are torqued down.







	Bedding	Cable	OD (B)		Entry Thread		Gland			Box
Code	Max (A)	Min	Мах	Armour Dia	Size (C)	Length (L1)	Length (L2)	A/F	A/C	QTY
PGPCWA25LS	19.8	20.3	27.5	1.25	M25 x 1.5	12.0	56.0	38.0	42.2	5
PGPCWA32LS	26.4	26.7	33.5	1.60	M32 x 1.5	12.0	60.0	46.0	51.0	5
PGPCWA40LS	32.4	33.0	40.9	1.60	M40 x 1.5	17.0	69.0	55.0	61.0	5
PGPCWA50sLS	38.0	39.4	46.3	2.00	M50 x 1.5	17.0	72.0	60.0	66.6	2
PGPCWA50LS	44.0	45.7	52.6	2.00	M50 x 1.5	17.0	72.0	65.0	72.1	2

ArmaKit[®] CW Ali Gland Kits

- For indoor or outdoor use.
- Three-part handling.

internal cone-and-ring.

· Precision manufactured from high quality aluminium.

Cable retention and earth continuity is achieved via mechanical clamping of the cable armour by the

- · Supplied in kits containing;
- M25-M32 2 glands, 2 locknuts, 2 earth tags, 2 LS shrouds
- •M40-M50 1 gland, 1 locknut, 1 earth tag, 1 LS shroud
- Standards: EN 60529
 - EN 50262

IP66 (If fitted with sealing washer) Temperature Range: -20°C to 70°C Material (Gland): Aluminium Material (Seal): Polychloroprene



All dimensions in mm except where stated