

METALLIC CABLE GLANDS | Cable Glands

BRASS CABLE GLANDS

ArmaKit Dome IP68 Glands PG

• Brass IP68 cable glands suitable for indoor & outdoor use.


Standards: EN 50262

Protection: IP68 3-5 bar

Temperature Range: -40°C to 100°C (static) (120° Instantaneous)

Material (Gland): Nickel-Plated Brass

Material (Seal): NBR Seal and EPDM O-Ring



Code	Cable Range (B)		Entry Thread Size	Gland		
	Min	Max		Length (L1)	Length (L2)	A/F
DOME-NP-PG7	2.0	5.0	PG7 x 1.27	6.5	23.5	14 / 15
DOME-NP-PG9	4.0	8.0	PG9 x 1.41	8.0	27.0	17 / 18
DOME-NP-PG11	5.0	10.0	PG11 x 1.41	8.0	29.0	20 / 21
DOME-NP-PG13.5	6.0	12.0	PG13.5 x 1.41	8.0	30.0	22 / 23
DOME-NP-PG16	10.0	14.0	PG16 x 1.41	8.5	31.5	24 / 25
DOME-NP-PG21	13.0	18.0	PG21 x 1.59	9.0	36.0	30
DOME-NP-PG29	18.0	25.0	PG29 x 1.59	10.0	41.0	40
DOME-NP-PG36	22.0	30.0	PG36 x 1.59	11.0	46.0	50
DOME-NP-PG42	32.0	38.0	PG42 x 1.59	13.0	50.0	57
DOME-NP-PG48	37.0	44.0	PG48 x 1.59	14.0	52.0	64



Call the Remora sales team at **01226 352 000**

Challenge us - We find a solution

Ident & Wiring Term
Copper Lugs
Heatshrink Repair
Cable Joining
Junction Boxes
Flexible Conduit
Cable Glands
Gland Accs.
Cable Cleats
Earthing Lightning
MCC Cable
Cable Ties & Acc
Tooling & Cable Prep
Fixing & Security