



### Pre Boxed Heatshrink Dispensers

With excellent electrical and mechanical properties, it is flexible and has a low shrinkage temperature. Applications include general electrical insulation, mechanical protection, cable and harness bundling, sleeving and colour identification. It is widely used in electrical, electronic, automotive, mechanical and general commercial industries. Remora's heat shrink boxed sleeving is available in sizes from 1.6mm to 25.4mm internal diameter and is available in nine different colours. Supplied in lengths from 3m to 15m in convenient point of sale packaging. Remora Heatshrink tube is also available handy sleeving kits or in Mini Kits.

- 2:1 Shrink Ratio
- High Specification, flame retardant, irradiated, flexible, polyolefin sleeving
- High electrical and chemical resistance
- Ideal for insulation, wire bundling and mechanical protection
- Available in a wide range of sizes and colours
- Packaged in boxes in 7 sizes from 1.6 to 25.4mm

**Shrink Temperature:** 80°C

**Temperature Range:** -40°C to 135°C

**Material:** Zero Halogen Polyolefin

**Colour:** Black, Blue, Brown, Clear, Grey, Green, Green/Yellow, Red, Yellow



Code	Internal Diameter		Shrunk Wall Thickness	Supplied Form	Fits Cable Lug Size mm²	Box Reel Length (m)
	Max Before Shrink	Min After Shrink				
HSB3-*	3.2	1.6	0.50	Round		15
HSB4-*	4.8	2.4	0.50	Round	1.5-2.5	10
HSB6-*	6.4	3.2	0.65	Round	4.0-6.0	10
HSB9-*	9.5	4.8	0.65	Flat 15	10	10
HSB13-*	12.7	6.4	0.65	Flat 20	16-35	8
HSB20-*	19.1	9.5	0.75	Flat 30	50-70	5
HSB25-*	25.4	12.7	0.9	Flat 40	95-150	3