

NON-METALLIC CONDUIT | Flexible Conduit Systems

FLEXIBLE CONDUIT ACCESSORIES

Push-Fit Straight Fitting - Polyamide

- Push-Fit design
- Straight glands are supplied including locknuts
- Available in Black and White

Temperature Range: -40°C to 105°C

Material: Polyamide 6

IP Rating: IP66

Colour: Black and White



Black Code	White Code	Thread Size	Conduit Size	Pack QTY
PF12		M12 x 1.5	12	10
PF16		M16 x 1.5	16	10
PF20	PF20-W	M20 x 1.5	20	10
PF25	PF25-W	M25 x 1.5	25	10
PF32		M32 x 1.5	32	10
PF40		M40 x 1.5	40	2
PF50		M50 x 1.5	50	2



Push-Fit 90° Elbow Fitting - Polyamide

- Push-Fit design
- 90° elbow fittings are supplied including locknuts
- Available in Black

Temperature Range: -40°C to 105°C

Material: Polyamide 6

IP Rating: IP66

Colour: Black



Black Code	Thread Size	Conduit Size	Pack QTY
EF12	M12 x 1.5	12	10
EF16	M16 x 1.5	16	10
EF20	M20 x 1.5	20	10
EF25	M25 x 1.5	25	10
EF32	M32 x 1.5	32	10
EF40	M40 x 1.5	40	2
EF50	M50 x 1.5	50	2



Conduit Cutting Tools

- Conduit cutting tool, ideal for cutting conduit 6mm to 42mm

Material: Steel



Code	Description	Cutting Capacity
CCT42	Conduit cutting tool	6 - 42



Ident & Wiring Term
Copper Lugs
Heatshrink Repair
Cable Joining
Junction Boxes
Flexible Conduit
Cable Glands
Gland Accs.
Cable Cleats
Earthing Lightning
MCC Cable
Cable Ties & Acc
Tooling & Cable Prep
Fixing & Security