

Heatshrink & Repair | HEATSHRINK SLEEVING

HEATSHRINK SLEEVING KITS

Ident & Wiring Terminals
 Copper Lugs
 Heatshrink Repair
 Cable Joining
 Junction Boxes
 Flexible Conduit
 Cable Glands
 Gland Accs.
 Cable Cleats
 Earthing & Lightning
 MCC Cable
 Cable Ties & Acc
 Tooling & Cable Prep
 Fixing & Security



Heatshrink Pack HSP6

Convenient and handy, Heatshrink Packs offer phase colours from 6mm to 25mm.

Shrink Temperature: 80°C

Temperature Range: -40°C to 135°C

Material: Zero Halogen Polyolefin

Colour: Black, Blue, Brown, Grey, Green/Yellow,



Code	Internal Diameter		Pack QTY	Heatshrink	
	Max Before Shrink	Min After Shrink		Length	Colour
HSP6	6.4	3.2	3	250	Black
	6.4	3.2	3	250	Blue
	6.4	3.2	3	250	Brown
	6.4	3.2	3	250	Grey
	6.4	3.2	3	250	Green/Yellow



Heatshrink Pack HSP12

Code	Internal Diameter		Pack QTY	Heatshrink	
	Max Before Shrink	Min After Shrink		Length	Colour
HSP12	12.7	6.4	3	250	Black
	12.7	6.4	3	250	Blue
	12.7	6.4	3	250	Brown
	12.7	6.4	3	250	Grey
	12.7	6.4	3	250	Green/Yellow



Heatshrink Pack HSP25

Code	Internal Diameter		Pack QTY	Heatshrink	
	Max Before Shrink	Min After Shrink		Length	Colour
HSP25	25.4	12.7	2	250	Black
	25.4	12.7	2	250	Blue
	25.4	12.7	2	250	Brown
	25.4	12.7	2	250	Grey
	25.4	12.7	2	250	Green/Yellow



Heatshrink Pack HSP

Code	Internal Diameter		Pack QTY	Heatshrink	
	Max Before Shrink	Min After Shrink		Length	Colour
HSP6-25	6.4	3.2	1	250	Black, Blue, Brown, Grey, Green/Yellow
	12.7	6.4	1	250	Black, Blue, Brown, Grey, Green/Yellow
	25.4	12.7	1	250	Black, Blue, Brown, Grey, Green/Yellow