


Cable Glands | GRIPLOC® NYLON CABLE GLANDS

METRIC GRIPLOC® NYLON CABLE GLANDS



GripLoc®



• Cap



• GripLoc Seal®



• Body



• Nitrile O-Ring



• Locknut (Included)



Multi-Hole Seals p.115

Nylon GripLoc Glands® Metric

- Standard Metric range of nylon cable glands.
- GripLoc Seal® - Superior Ingress Protection, mechanical grip and cable retention.
- Supplied Complete with Locknuts.
- Vibration-Lock - Suitable for high vibration environments..


Standards: EN 50262

Protection: IP69K / IP68 10 bar (150 PSI)

Temperature Range: -40°C to 100°C (static)

Material (Gland): PA (Nylon) UL 94 V2

Material (Seal): NBR Seal and EPDM O-Ring



| Code | Cable Range (B) | | Entry Thread | Gland | | A/F | Pack QTY |
|----------------|-----------------|------|--------------|-------------|-------------|-------|----------|
| | Min | Max | Size | Length (L1) | Length (L2) | | |
| GripLoc-M12-* | 3.0 | 6.5 | M12 x 1.5 | 8.0 | 29.0 | 15.0 | 10 |
| GripLoc-M16-* | 4.0 | 8.0 | M16 x 1.5 | 8.0 | 30.0 | 19.0 | 10 |
| GripLoc-M20s-* | 5.0 | 9.0 | M20 x 1.5 | 9.0 | 36.0 | 24.0 | 10 |
| GripLoc-M20* | 6.0 | 12.0 | M20 x 1.5 | 9.0 | 36.0 | 24.0 | 10 |
| GripLoc-M20L-* | 10.0 | 14.0 | M20 x 1.5 | 9.0 | 37.0 | 27.0 | 10 |
| GripLoc-M25-* | 13.0 | 18.0 | M25 x 1.5 | 11.0 | 42.0 | 33.0 | 10 |
| GripLoc-M32-* | 18.0 | 25.0 | M32 x 1.5 | 11.0 | 50.0 | 42.0 | 10 |
| GripLoc-M40-* | 22.0 | 32.0 | M40 x 1.5 | 13.0 | 61.0 | 53.0 | 10 |
| GripLoc-M50-* | 32.0 | 38.0 | M50 x 1.5 | 13.0 | 62.0 | 60.0 | 10 |
| GripLoc-M63-* | 37.0 | 44.0 | M63 x 1.5 | 14.0 | 63.0 | 68.0 | 10 |
| GripLoc-M63L-* | 35.0 | 47.0 | M63 x 1.5 | 15.0 | 68.0 | 70.0 | 10 |
| GripLoc-M75-* | 48.0 | 56.0 | M75 x 2.0 | 25.0 | 94.0 | 69.0 | 2 |
| GripLoc-M90-* | 57.0 | 76.0 | M90 x 2.0 | 25.0 | 87.0 | 110.0 | 2 |

Nylon GripLoc Glands® Metric - Long Thread

- Long Thread Metric range of nylon cable glands.
- GripLoc Seal® - Superior Ingress Protection, mechanical grip and cable retention.
- Supplied Complete with Locknuts.
- Vibration-Lock - Suitable for high vibration environments.


Standards: EN 50262

Protection: IP69K / IP68 10 bar (150 PSI)

Temperature Range: -40°C to 100°C (static)

Material (Gland): PA (Nylon) UL 94 V2

Material (Seal): NBR Seal and EPDM O-Ring



| Code | Cable Range (B) | | Entry Thread | Gland | | A/F | Pack QTY |
|------------------|-----------------|------|--------------|-------------|-------------|------|----------|
| | Min | Max | Size | Length (L1) | Length (L2) | | |
| GripLoc-LTM12-* | 3.0 | 6.5 | M12 x 1.5 | 15.0 | 36.0 | 15.0 | 10 |
| GripLoc-LTM16-* | 4.0 | 8.0 | M16 x 1.5 | 15.0 | 37.0 | 19.0 | 10 |
| GripLoc-LTM20s-* | 5.0 | 9.0 | M20 x 1.5 | 15.0 | 42.0 | 24.0 | 10 |
| GripLoc-LTM20* | 6.0 | 12.0 | M20 x 1.5 | 15.0 | 42.0 | 24.0 | 10 |
| GripLoc-LTM20L* | 10.0 | 14.0 | M20 x 1.5 | 15.0 | 43.0 | 27.0 | 10 |
| GripLoc-LTM25-* | 13.0 | 18.0 | M25 x 1.5 | 15.0 | 46.0 | 33.0 | 10 |
| GripLoc-LTM32-* | 18.0 | 25.0 | M32 x 1.5 | 15.0 | 54.0 | 42.0 | 10 |
| GripLoc-LTM40-* | 22.0 | 32.0 | M40 x 1.5 | 18.0 | 66.0 | 53.0 | 10 |
| GripLoc-LTM50-* | 32.0 | 38.0 | M50 x 1.5 | 18.0 | 67.0 | 60.0 | 10 |
| GripLoc-LTM63-* | 37.0 | 44.0 | M63 x 1.5 | 18.0 | 67.0 | 68.0 | 10 |
| GripLoc-LTM63L* | 35.0 | 48.0 | M63 x 1.5 | 18.0 | 71.0 | 70.0 | 10 |

GripLoc® brand cable glands are offered for sale exclusively in the United Kingdom by Remora Electrical Limited.