



P-Clips - Nylon


P-Clips are designed to hold cables, tubes and components in domestic appliances, electronics and electric apparatus generally.

To apply, just clamp down on loosen cables and screw it to chassis

Material: Nylon 66

Operating Temperature: -40°C to 85°C

Colour: Black



| Code | Colour | (A) | (B) | (C) | Dia (D) | Pack QTY |
|-------|--------|------|------|------|---------|----------|
| NPC5 | Black | 9.2 | 9.6 | 1.10 | 5.0 | 100 |
| NPC6 | Black | 10.4 | 10.1 | 1.10 | 6.3 | 100 |
| NPC9 | Black | 12.5 | 12.3 | 1.40 | 9.5 | 100 |
| NPC12 | Black | 14.8 | 12.2 | 1.40 | 12.7 | 100 |



P-Clips - Nylon Box Kit

Assorted range of P-Clips covering 3.1-28.5mm diameter supplied in a Box Kit.

Material: Nylon 66

Operating Temperature: -40°C to 85°C

Colour: Black




| Code | Description | Size Range |
|------|----------------------------------|------------|
| BK10 | 6 Compartment / Approx 210 Items | 3.1 - 28.5 |

Stainless Steel Cable Tie Mounts

Stainless Cable Tie Mounts are designed to meet the requirements of BS 7671 in conjunction with stainless steel cable ties. These can be simply installed with a M4 or M6 screw or bolt.

Material: 316 Stainless Steel

Operating Temperature: -80°C to 530°C



| Code | Bolt Size | (A) | (B) | (C) | (D) | (F) | Max Tie Width (E) | Pack QTY |
|--------|-----------|------|------|------|-----|-----|-------------------|----------|
| SSCTM1 | M4 | 29.2 | 15.0 | 18.8 | 5.0 | 4.2 | 10.0 | 100 |
| SSCTM2 | M6 | 29.2 | 15.0 | 18.8 | 5.0 | 6.2 | 10.0 | 100 |

