RELEASABLE CABLE TIES | Cable Ties & Banding

STAINLESS STEEL CABLE TIES



Buckle Lock Ties

316 Stainless Steel Buckle Ties

PPA coated AE cable ties feature a buckle type locking mechanism. This provides a quick and easy application which can be unfastened for re-using. The PPA 571 coating is low smoke, zero halogen which offers superior corrosion resistance. Suitable for multiple installations over long periods of time in harsh environments such as marine, oil exploration and mining.


316 Stainless Steel AE Cable Ties

- Available in two widths 6.4mm & 9.6mm
- Low smoke, Zero Halogen PPA coated for superior corrosion resistance
- Thick coating protected cables and hands
- · Fast, easy application
- Vibration proof
- Colours available upon request subject to MOQ
- Reusable

Temperature Range: -75°C to 105°C Material: 316 Stainless Steel

Coating: Low Smoke, Zero Halogen PPA 571 Coating













				Loop Tensile	
Code	Length (A)	Width (B)	Max Bundle Dia.	Strength (Kg)	Double Wrapped (kg)
AE111	152.0	6.40	38.0	34.0	136.0
AE112	229.0	6.40	63.0	34.0	136.0
AE113	305.0	6.40	86.0	34.0	136.0
AE114	457.0	6.40	137.0	34.0	136.0
AE115	610.0	6.40	185.0	34.0	136.0
AE311	152.0	9.60	38.0	45.0	136.0
AE312	229.0	9.60	63.0	45.0	136.0
AE313	305.0	9.60	86.0	45.0	136.0
AE314	457.0	9.60	137.0	45.0	136.0
AE315	610.0	9.60	185.0	45.0	136.0
AE316	762.0	9.60	231.0	45.0	136.0
AE317	914.0	9.60	280.0	45.0	136.0

Manual Tensioning Hook

Used to tension Ties and Multi-Lok Ties. Material: Steel



Code



Descript	ion

Hand tensioning hook for AE reusable cable ties AE201



Call the Remora sales team at 01226 352 000

Challenge us - We find a solution

Cable Glands

Tooling

Jointing

Heat-shrink

Conduit