


ELECTRICAL TAPES | Heatshrink & Repair

TAPES and UNDERGROUND MARKING

PVC Insulating Tape - Phase Kit

Convenient Phase Colours PVC Tape packs available in two length 20 & 33 metre.

PVC Phase Kits include ;
2 x Black , Blue, Brown & Grey
1 x White & Green/Yellow



Code	Width	Length (m)	Thickness
PVC-PHASE1	19.0	20	0.15
PVC-PHASE2	19.0	33	0.15

Self Amalgamating Tape

A highly conformable, self-amalgamating EPR (Ethylene Propylene Rubber) based tape for electrical applications, jointing and cable repairs.

This high voltage rubber tape provides a seamless waterproof, electrically stable insulation layer, it sticks only to itself so a requirement of 50% overlap must be used.

- Good solvent resistance
- Stretch up to 100% for void-free, moisture-resistant insulation
- Unaffected by UV light
- 2:1 Shrink Ratio
- Zero Halogen

Material: EPDM

Tensile Strength: 4.73Mpa

Dielectric Strength: 25kV/mm

Operating Temperature: 90°C



Code	Width	Length (m)	Thickness	Colour
SAT19-10	19.0	10	0.50	Black
SAT25-10	25.0	10	0.50	Black

Petroleum Anti-Corrosion Tape

PETRO is a cold-applied anti-corrosion sealing tape that is petroleum impregnated and coated. It offers a weatherproof seal when wrapped around joints to stop the ingress of moisture.

Material: Synthetic - Impregnated and coated with neutral petroleum compound

Colour: Green



Code	Width	Length (m)
PETRO-50	50.0	10
PETRO-100	100.0	10



Ident & Wiring term

Copper Lugs

Heatshrink Repair

Cable Jointing

Junction Boxes

Flexible Conduit

Cable Glands

Gland Accs.

Cable Cleats

Earthing Lightning

MCC Cable

Cable Ties & Acc

Tooling & Cable Prep

Fixing & Security