


# Accessories | HAZARDOUS AREA DOME STOPPING PLUGS

## HAZARDOUS AREA DOME STOPPING PLUGS

Ident & Wing Term  
Copper Lugs  
Heatshrink Repair  
Cable Joining  
Junction Boxes  
Flexible Conduit  
Cable Glands  
Gland Accs.  
Cable Cleats  
Earthing Lightning  
MCC Cable  
Cable Ties & Acc  
Tooling & Cable Prep  
Fixing & Security



### Metric Hazardous Dome Head Stopping Plug - Brass

- ISO Metric range.
  - Application; Hazardous Area, Machines, Devices, Housings, Panels
- Equipment Protection Levels:**  
IECEX: Ex db I Mb / Ex eb I Mb / Ex db IIC Gb / Ex eb IIC Gb / Ex ta IIIC Da / Ex nR IIC  
ATEX: Ⓜ I M2 Ex db I Mb / Ex eb I Mb, Ⓜ II 2G 1D Ex db IIC Gb / Ex eb IIC Gb / Ex ta IIIC Da

**Protection:** IP66 / IP68  
**Temperature Range:** -60°C to 95°C (-60°C to 160°C with High Temp Gasket)  
**Material:** Brass or Nickel Plated Brass (Marine Grade)



Code	Entry Thread	Thread Length (L1)	Head Diameter	Allen Key AF
353016-UN	M16 x 1.5	16.0	22.0	10.0
353020-UN	M20 x 1.5	16.0	25.0	10.0
353025-UN	M25 x 1.5	16.0	35.0	10.0
353032-UN	M32 x 1.5	16.0	42.0	10.0
353040-UN	M40 x 1.5	16.0	50.0	10.0
353050-UN	M50 x 1.5	16.0	60.0	10.0
353063-UN	M63 x 1.5	16.0	70.0	14.0
353075-UN	M75 x 1.5	16.0	85.0	14.0
353080-UN	M80 x 2.0	20.0	90.0	14.0
353090-UN	M90 x 2.0	20.0	100.0	14.0
353100-UN	M100 x 2.0	20.0	110.0	14.0

- For Nickel Plated remove -UN when ordering

### Metric Hazardous Dome Head Stopping Plug - Nylon

- ISO Metric range.
  - Application; Machines, Devices, Housings, Panels
- Standards:** IECEX: : Ex eb IIC Gb, Ex tb IIIC Db, Ex nR IIC Gc  
ATEX: Ⓜ II 2GD, Ex eb IIC Gb, Ex tb IIIC Db, Ex nR IIC Gc

**Protection:** IP66 / IP68  
**Temperature Range:** -20°C to 95°C  
**Material:** HDPE, Nylon



Code	Entry Thread	Thread Length (L1)	Head Diameter	Allen Key AF
352716	M16 x 1.5	15.0	20.5 (min)	6.0
352720	M20 x 1.5	12.0	28.0 (min)	10.0
352725	M25 x 1.5	15.0	33.0 (min)	10.0
352732	M32 x 1.5	15.0	40.0 (min)	10.0
352740	M40 x 1.5	15.0	48.0 (min)	14.0
352750	M50 x 1.5	15.0	56.0 (min)	19.0
352763	M63 x 1.5	15.0	69.0 (min)	19.0
352775	M75 x 1.5	15.0	81.0 (min)	19.0