

HYDRAULIC CRIMP and CUTTING TOOLING

Hydraulic Crimping & Cutting Tools

Ident & Wiring Term
Copper Lugs
Heatshrink Repair
Cable Joining
Junction Boxes
Flexible Conduit
Cable Glands
Gland Accs.
Cable Cleats
Earthing Lightning
MCC Cable
Cable Ties & Acc
Tooling & Cable Prep
Fixing & Security



Hydraulic Hexagon Crimping Head 35.0 to 630.0mm²

The TorqTek HCH630 tool has a heavy duty hydraulic hexagon crimping head for uninsulated copper tube terminals from 35.0 to 630.0mm². Supplied in a sturdy carry case and complete with HFP hydraulic foot pump. Manufactured from forged alloy steel, the crimp dies are precision designed and supplied from 35 to 630mm²

HCH630 Head

Crimping Range: 35.0 to 630.0mm²

Length: 350mm

Weight: 11.0Kgs

HFP Foot Pump

Max Output Pressure: 1st Stage 20Kg² / 2nd Stage 700Kg²

Oil Output: 13ml Low Pressure / 2.8ml High Pressure

Oil Capacity: 700cc

Weight: 12.5Kgs



Code	Description	Tool Length	Crimping Capacity (mm ²)
HCH630-HFP	Hydraulic Hexagon Crimping Head	350.0	35.0 - 630.0



Hydraulic Cutting Head up to 100mm Diameter

The TorqTek HCH100 hydraulic cutting head tool for suitable for cables up to 100mm diameters. The head can be easily opened to cut running cables and the handle allows comfortable positioning of the head onto the cable to be cut. Supplied in a sturdy carry case and complete with HFP hydraulic foot pump.

HCH100 Head

Cutting Range: up to 100mm diameter

Cutting Force: 60KN

Oil Capacity: 15ml

Length: 515mm

Weight: 8.40Kgs

HFP Foot Pump

Max Output Pressure: 1st Stage 20Kg² / 2nd Stage 700Kg²

Oil Output: 13ml Low Pressure / 2.8ml High Pressure

Oil Capacity: 700cc

Weight: 12.5Kgs



Code	Description	Tool Length	Cutting Capacity (mm OD)
HCH100-HFP	Hand Hydraulic Cutting Tool	515.0	up to 100.0

