

NPT-Metric Hazardous Adaptors

Enlarges housing entry thread.

- NPT - ISO Metric range.

- Application; Hazardous Area, Machines, Devices, Housings, Panels

Equipment Protection Levels:

IECEX/INMETRO: Ex db I Mb / Ex eb I Mb / Ex db IIC Gb / Ex eb IIC Gb / Ex ta IIC Da / Ex nR IIC

ATEX: Ⓜ I M2 Ex db I Mb / Ex eb I Mb, Ⓜ II 2G 1D Ex db IIC Gb / Ex eb IIC Gb / Ex ta IIC Da

Protection: IP65 / IP66



Temperature Range: -60°C to 95°C

Material: Brass or Nickel Plated Brass (Marine Grade)



Code	Entry Thread		Thread Length				Hex Length
	Male	Female	Male (L1)	Female (F)	A/F	A/C	Min (G)
AN050M20E-UN	½" / 0.50 NPT	M20 x 1.5	15.0	15.0	27.0	30.4	21.0
AN075M25E-UN	¾" / 0.75 NPT	M25 x 1.5	15.0	15.0	32.0	36.0	21.0

- For Nickel Plated remove -UN when ordering



Ident. & Wiring Term
Copper Lugs
Heatshrink Repair
Cable Joining
Junction Boxes
Flexible Conduit
Cable Glands
Gland Accs.
Cable Cleats
Earthing Lightning
MCC Cable
Cable Ties & Acc
Tooling & Cable Prep
Fixing & Security



Call the Remora sales team at 01226 352 000

Challenge us - We find a solution