

# Joining | CABLE DUCT SEALING SYSTEM

## RE-ENTERABLE CABLE DUCT SEALING SYSTEM

# FiloSeal+HD

## Re-enterable Duct Sealing System

FiloSeal+HD provides a strong support system using the hexagonal tubes which builds up like a honeycomb structure. FiloSeal+HD is suitable for sealing any cable configuration or pipes contained in one duct and also allows easy re-entry of the seal to add or remove cables or pipes as required. The duct sealing system FiloSeal+HD uses our MD+ sealant which is easily applied from a skeleton gun. The high quality, one component, flexible sealant "MD+" is based on a Silicone compound that cures with air (Humidity). After application and full curing the thixotropic MD+ forms a plastic elastomer mass with special qualities effectively sealing and bonding, while providing a high level of durability.



### Re-Enterable Duct Sealing System

- Flexible, one component, adhesive and sealing compound
- High levels of Gas and Water tightness
- Resistant against Water, Alkaline, Chemical agents
- Resistant to Rats
- Resistant to Hydrogen Sulphide / Methane and many other Gases (NedLab)
- Non corrosive
- Shock absorbing
- Non toxic, neutral and almost odourless
- Complies with ATEX regulations
- Suitable for any shaped duct / bore hole / opening
- Quick and easy installation
- Seals all known materials, PVC & PE sheathed cables, PILC, (HD) PE pipes
- Suitable for renovations, can be installed retrospectively

**Density:** 1.2 gr/cm<sup>3</sup>

**Pressure:** up to 2 bar

**Pulling Force:** 100kg

**Flow:** <2mm ISO 7390

**Colour:** Red-Brown

**Skin Over Time:** +-15minutes

**Curing Time:** 3mm / 24 hours

**Hardness:** 30 shore A - DIN 53505

**Elongation:** 100% - DIN53504

**Tensile Strength:** 0.8 N/mm<sup>2</sup> - DIN53504

**Operating Temp:** +5°C to 40°C

**Temperature Resistance:** -40°C to 120°C



Code	Description	Max Duct Diameter mm	Max Cable Diameter in Duct	Pressure Resistance
FS+HD-110	FiloSeal+HD 110mm	Max 110.0	Ø 80 Max	Upto 2 bar
FS+HD-160	FiloSeal+HD 160mm	Max 160.0	Ø 130 Max	Upto 2 bar



# FiloSeal+ Duct Sealing System

### Re-Enterable Duct Sealing System

All the benefits of the FiloSeal+ with the exception of reduced max pressure resistance of 1 bar and minimal pull resistance.



Code	Description	Max Duct Diameter mm	Max Cable Diameter in Duct	Pressure Resistance
FS+125	FiloSeal+ 125mm	Max 125.0	Ø 95 Max	Upto 1 bar
FS+200	FiloSeal+ 200mm	Max 200.0	Ø 160 Max	Upto 1 bar