

### Metric-Metric Industrial Adaptors

- ISO Metric range.
- Application; Machines, Devices, Housings, Panels


**Standards:** EN 50262

**Protection:** IP54


IP66 (if fitted with sealing washer)

**Temperature Range:** -60°C to 200°C

**Material:** Nickel Plated Brass



Code	Entry Thread		Thread Length		
	Male	Female	Male (L1)	Female (F)	A/F
AM12M16S	M12 x 1.5	M16 x 1.5	5.0	13.0	18.0
AM16M20S	M16 x 1.5	M20 x 1.5	13.0	13.0	24.0
AM20M25S	M20 x 1.5	M25 x 1.5	13.0	13.0	29.0
AM25M32S	M25 x 1.5	M32 x 1.5	13.0	13.0	36.0
AM32M40S	M32 x 1.5	M40 x 1.5	13.0	15.0	44.0
AM40M50S	M40 x 1.5	M50 x 1.5	13.0	15.0	54.0
AM50M63S	M50 x 1.5	M63 x 1.5	13.0	15.0	67.0
AM63M75S	M63 x 1.5	M75 x 1.5	13.0	18.0	79.0



### PG-Metric Industrial Adaptors

- PG-ISO Metric range.
- Application; Machines, Devices, Housings, Panels

**Standards:** EN 50262

**Protection:** IP54


IP66 (if fitted with sealing washer)

**Temperature Range:** -60°C to 200°C

**Material:** Nickel Plated Brass



Code	Entry Thread		Thread Length		
	Male	Female	Male (L1)	Female (F)	A/F
APG9M16S	PG9 x 1.41	M16 x 1.5	13.0	13.0	24.0
APG9M20S	PG9 x 1.41	M20 x 1.5	13.0	13.0	24.0
APG11M16S	PG11 x 1.41	M16 x 1.5	13.0	13.0	24.0
APG11M20S	PG11 x 1.41	M20 x 1.5	13.0	13.0	24.0
APG13M20S	PG13.5 x 1.41	M20 x 1.5	13.0	13.0	24.0
APG13M25S	PG13.5 x 1.41	M25 x 1.5	13.0	13.0	24.0
APG16M25S	PG16 x 1.41	M25 x 1.5	13.0	13.0	29.0
APG21M32S	PG21 x 1.59	M32 x 1.5	13.0	13.0	36.0
APG29M40S	PG29 x 1.59	M40 x 1.5	13.0	15.0	44.0
APG36M50S	PG36 x 1.59	M50 x 1.5	13.0	15.0	54.0
APG42M63S	PG42 x 1.59	M63 x 1.5	13.0	15.0	70.0



Sealing Washers  
Supplied Separately p.180

Call the Remora sales team at **01226 352 000**

Challenge us - We find a solution