

Heatshrink & Repair | SLEEVING

PUSH BACK SLEEVING & SPIRAL WRAP

Push Back Braided Sleeving

Braided sleeving is a range of lightweight, self-fitting, flexible sleeving that provides tough protection for bundles of cables up to a maximum diameter of 80mm. Low toxicity and halogen free with an expansion ratio of 1.5 times original dimensions.

- Unaffected by most chemical, solvents and oils.
- UV and abrasion resistant.

Material: Heat Stabilised Polyester (PET)
Continuous Temperature: -50°C to +150°C
Flammability: Self-extinguishing material



Code	Diameter	Flat Diameter	Reel QTY (m)
BS5/100-B	3 - 9	6	100
BS10/100-B	5 - 16	8	100
BS15/50-B	10 - 28	16	50
BS20/50-B	14 - 30	20	50
BS25/50-B	18 - 35	25	50
BS30/25-B	20 - 50	32	25
BS40/25-B	25 - 60	38	25
BS50/25-B	40 - 80	50	25



Spiral Wrap Binding

Lightweight flexible spiral wrap binding provides a fast, flexible and economical way to organise and protect cables. Wrapping can be cut to fit and easily reused as it keeps spiral form.

- Water, oils and fuel resistant
- Halogen free
- Easily applied to electrical harnesses and cable bundles

Material: Polyethylene
Continuous Temperature: -30°C to +90°C



Code	Colour	Inside Diameter	Outside Diameter	Min. Bundle Dia	Max. Bundle Dia	Length (m)
CB1-B	Black	5.0	6.0	4.0	50.0	25
CB2-B	Black	7.0	8.0	6.0	60.0	25
CB3-B	Black	10.0	12.0	9.0	65.0	25
CB4-B	Black	13.0	15.0	12.0	70.0	25
CB5-B	Black	21.0	24.0	20.0	130.0	25
CB1-N	Natural	5.0	6.0	4.0	50.0	25
CB2-N	Natural	7.0	8.0	6.0	60.0	25
CB3-N	Natural	10.0	12.0	9.0	65.0	25
CB4-N	Natural	13.0	15.0	12.0	70.0	25
CB5-N	Natural	21.0	24.0	20.0	130.0	25

All dimensions in mm except where stated