



LOCKNUTS

Ident & Wing Term
Copper Lugs
Heatshrink Repair
Cable Jointing
Junction Boxes
Flexible Conduit
Cable Glands
Gland Accs.
Cable Cleats
Earthing Lightning
MIBC Cable
Cable Ties & Acc
Tooling & Cable Prep
Fixing & Security




Stainless Steel Locknuts

Stainless Steel Locknuts are recommended for use where prolonged submersion or increased corrosion resistance is required. Manufactured from 316 (A4) Stainless Steel.

Temperature Range: -100°C to 400°C

Material: 316 (A4) Stainless Steel



Metric

Stainless

Code	Entry Thread	A/F	A/C	Thickness	Pack QTY
SSLN12	M12 x 1.5	15.0	16.5	3.0	100
SSLN16	M16 x 1.5	22.0	24.0	4.0	100
SSLN1	M20 x 1.5	25.4	27.9	4.0	100
SSLN2	M25 x 1.5	30.0	33.0	4.0	100
SSLN3	M32 x 1.5	40.0	44.0	4.0	100
SSLN4	M40 x 1.5	46.0	50.5	4.8	50
SSLN5	M50 x 1.5	65.0	71.5	5.0	25
SSLN6	M63 x 1.5	80.0	88.0	6.4	25
SSLN7	M75 x 1.5	90.0	99.0	7.0	10
SSLN8	M80 x 2.0	90.0	99.0	9.0	2
SSLN9	M90 x 2.0	104.8	115.3	9.0	2
SSLN10	M100 x 2.0	114.3	125.7	9.0	2

NPT

Code	Entry Thread	A/F	A/C	Thickness	Pack QTY
SSLN050NPT	½" NPT	27.0	29.7	3.2	100
SSLN075NPT	¾" NPT	30.5	33.5	4.0	100
SSLN100NPT	1" NPT	36.0	39.5	6.4	100
SSLN125NPT	1½" NPT	46.0	50.5	6.4	100
SSLN150NPT	1½" NPT	55.0	60.6	6.4	100
SSLN200NPT	2" NPT	65.0	70.8	6.4	50
SSLN250NPT	2½" NPT	90.0	99.0	9.0	50
SSLN300NPT	3" NPT	104.8	115.3	9.0	25
SSLN350NPT	3½" NPT	114.3	125.7	10.0	10

Aluminium Locknuts

Aluminium Locknuts are recommended when installing aluminium Cable Glands to prevent the galvanic corrosion which can occur when dissimilar metals are coupled together.

Temperature Range: -60°C to 130°C

Material: Aluminium 6082 HE30



Aluminium

Code	Entry Thread	A/F	A/C	Thickness	Pack QTY
ALN16	M16 x 1.5	24.0	36.4	4.0	100
ALN1	M20 x 1.5	27.0	29.7	4.0	100
ALN2	M25 x 1.5	30.0	33.0	4.0	100
ALN3	M32 x 1.5	40.0	44.0	4.0	100
ALN4	M40 x 1.5	50.0	55.0	4.5	100
ALN5	M50 x 1.5	65.0	71.5	5.0	50
ALN6	M63 x 1.5	75.0	82.5	6.5	25
ALN7	M75 x 1.5	90.0	99.0	7.0	10