



Fixing Band

Multi-Purpose Fixing Band

Multi-Purpose Fixing Band is a versatile product used in many applications. It is available in three widths 12, 17 & 26mm manufactured from Carbon Steel coated as standard used to secure cables, pipes, ducts & conduits. Available bare galvanised (G) or coated in Black (B), White (W), Red (R) and Orange (O). Other materials offered are Copper and Stainless Steel.

Multi-Purpose Fixing Band

- High tensile strength
- Corrosion resistance
- Coating is kind to hands/cable
- Easy to form around any section

Temperature Range: -15°C to 50°C

Material: Carbon Steel / PE Coated

Standards: BS 7671:2018



Standard						Max Working
Code	Width (W)	Length (m)	Thickness	Fixing Hole Dia (F)	Centers (L1)	Load (Kg)
ARB12G	12.0	10.0	0.8	5.0	15.0	75.0
ARB12B	12.0	10.0	0.8	5.0	15.0	75.0
ARB12R	12.0	10.0	0.8	5.0	15.0	75.0
ARB12W	12.0	10.0	0.8	5.0	15.0	75.0
ARB17G	17.0	10.0	0.8	7.0	20.0	95.0
ARB17B	17.0	10.0	0.8	7.0	20.0	95.0
ARB17R	17.0	10.0	0.8	7.0	20.0	95.0
ARB17W	17.0	10.0	0.8	7.0	20.0	95.0
ARB26G	26.0	10.0	0.8	8.0	28.0	200.0
ARB26B	26.0	10.0	0.8	8.0	28.0	200.0

304 Stainless Steel

- Increased tensile strength and operating temperature

Temperature Range: -60°C to 160°C

Material: 304 Stainless Steel



Stainless Steel					Max Working
Code	Width (W)	Length (m)	Thickness	Fixing Hole Dia (F)	Load (Kg)
ARB12SS	12.0	10.0	0.8	5.0	75.0
ARB17SS	17.0	10.0	0.8	7.0	95.0

Copper

- Increased conductivity

Temperature Range: -15°C to 50°C

Material: Copper / Brass



Copper		Dimensions				Max Working
Code	Length (m)	(W)	(F)	(L1)	Thickness	Load (Kg)
ARB12C	10.0	12.0	5.0	5.0	0.8	65.0
ARB17C	10.0	17.0	7.0	7.0	0.8	85.0

