


# Accessories | INDUSTRIAL AREA DOME STOPPING PLUGS

## NYLON DOME HEAD STOPPING PLUGS



### Metric Nylon Dome Head Stopping Plugs

Remora industrial dome head stopping plugs are designed as a cost effective permanent solution for blanking unused pre-threaded holes. A 'cross' slot in the cap enables tightening with a screwdriver.

**Protection:** IP56

IP66 / IP68 (if fitted with sealing washer)


**Temperature Range:** -20°C to 100°C (static)

**Material:** Polystyrene, Impact Resistant

**Colour:** Grey



Code	Entry Thread	Thread Length (L1)	Cap Diameter (A)
EVS12	M12 x 1.5	8.0	15.0
EVS16	M16 x 1.5	9.0	19.0
EVS20	M20 x 1.5	9.5	25.0
EVS25	M25 x 1.5	11.5	30.0
EVS32	M32 x 1.5	12.0	38.0
EVS40	M40 x 1.5	13.0	46.0
EVS50	M50 x 1.5	15.0	56.0
EVS63	M63 x 1.5	17.0	68.0



### PG Nylon Dome Head Stopping Plugs

Remora industrial dome head stopping plugs are designed as a cost effective permanent solution for blanking unused pre-threaded holes. A 'cross' slot in the cap enables tightening with a screwdriver.

**Protection:** IP56

IP66 / IP68 (if fitted with sealing washer)

**Temperature Range:** -20°C to 100°C (static)

**Material:** Polystyrene, Impact Resistant

**Colour:** Grey



Code	Entry Thread	Thread Length (L1)	Cap Diameter (A)
VS7	PG7 x 1.27	8.0	15.0
VS9	PG9 x 1.41	9.0	19.0
VS11	PG11 x 1.41	10.0	22.0
VS13	PG13.5 x 1.41	10.0	25.0
VS16	PG16 x 1.41	9.5	27.0
VS21	PG21 x 1.59	12.0	33.0
VS29	PG29 x 1.59	12.0	44.0
VS36	PG36 x 1.59	15.0	55.0
VS42	PG42 x 1.59	16.0	62.0
VS48	PG48 x 1.59	16.0	68.0



Sealing Washers  
Supplied Separately p.180