


# Cable Glands | GRIPLOC® NYLON CABLE GLANDS

## METRIC GRIPLOC® NYLON ATEX IECEX CABLE GLANDS



### Nylon ATEX IECEX Exe Glands™ Metric

- ATEX Exe Metric range of nylon cable glands.
  - For Hazardous Locations
- Standards:** EN 60079-0, EN 60079-7, EN 60079-31  
**Device Group:** II  
**Category:** 2 and 3  
**Atmosphere:** G/D  
**Zone:** 1, 2 - 21, 22  
**Temperature Range:** -20°C to 80°C (static)  
**Material (Gland):** PA (Nylon) UL 94 V2  
**Material (Seal):** Silicone  
**Protection:** IP66 / IP68



Code	Cable Range (B)		Entry Thread Size	Gland		A/F	Pack QTY
	Min	Max		Length (L1)	Length (L2)		
GripLoc-EX-M12	3.0	6.5	M12 x 1.5	8.0	29.0	15.0	10
GripLoc-EX-M16	6.0	8.0	M16 x 1.5	8.0	30.0	19.0	10
GripLoc-EX-M20	6.0	12.0	M20 x 1.5	9.0	36.0	24.0	10
GripLoc-EX-M25	13.0	18.0	M25 x 1.5	11.0	42.0	33.0	10
GripLoc-EX-M32	18.0	25.0	M32 x 1.5	11.0	48.0	42.0	10
GripLoc-EX-M40	22.0	32.0	M40 x 1.5	13.0	61.0	53.0	5
GripLoc-EX-M50	32.0	38.0	M50 x 1.5	13.0	62.0	60.0	5
GripLoc-EX-M63	37.0	44.0	M63 x 1.5	14.0	62.0	68.0	2



• Cap



• Seal



• Body



• Nitrile O-Ring



• Locknut



GripLoc® brand cable glands are offered for sale exclusively in the United Kingdom by Remora Electrical Limited.